



Ablemail Electronics

A Division of Merlyn Electronics

Merlyn House,
Bridge Mills,
Holland Street,
Salford, M6 6EL
Tel: +44(0)161 745 7697
Fax: +44(0)161 737 5615
info@ablemail.co.uk
www.ablemail.co.uk

AMI24-12-24AUX

DESCRIPTION

This unit is a water resistant switching type voltage converter intended for use on vehicles with a 24V electrical system to power an independently isolated 12V supply of either polarity. The unit also includes an independently isolated low power converter which may be used as a continuous supply for memory maintenance. The unit can deliver 24A continuous and 30A intermittent output load current and has output overload and over temperature protection with a fully automatic reset. The unit provides total galvanic isolation of the 12V output from the 24V input. The unit is assembled in an aluminium extruded case and encapsulated in silicone rubber. This allows for reliable operation in harsh vehicle environments and areas of high ambient temperatures. This unit is available with suffix P to meet Institute of Petroleum DOC - 1.92.1 for use on hazardous vehicles.

EMC

Type approved to 72/245/EEC as last amended by 95/54/EC.

INPUT VOLTAGE

24 Volt nominal vehicle supply (20-32V).

OUTPUT VOLTAGE

Main: 12V $\pm 5\%$ @ 24A
Aux: 13.5V $\pm 5\%$ @ 40mA

OUTPUT LOAD CURRENT

Main: 24A continuous 30A intermittent.
Aux: 40mA continuous 2A intermittent.

NO LOAD INPUT CURRENT

Main: Maximum 160mA typical 70mA @ 24V input.
Aux: 10mA @ 24V input.

PROTECTION

Output overload and over temperature protection with fully automatic reset.

OPERATING TEMPERATURE

Maximum 70°C. Minimum -30°C

SIZE AND WEIGHT

Length: 180mm Height: 40mm Width: 124mm
552g

CONNECTIONS

200mm flying leads of thin wall auto cable.

24V Input

Positive	red
Negative	black
Aux	white

12V Output

Positive	blue
Negative	green
Aux	yellow