



Ablemail Electronics

A Division of Merlyn Electronics

Merlyn House,
Bridge Mills,
Holland Street,
Salford, M6 6EL
Tel: +44(0)161 745 7697
Fax: +44(0)161 737 5615
info@ablemail.co.uk
www.ablemail.co.uk

AMN24-12-6AUX

DESCRIPTION

This unit is a switching type voltage converter intended for use on vehicles with a 24V electrical system to power accessories designed for use on a 12V vehicle electrical system. The unit includes the addition of an independent low power converter which may be used as a continuous supply for memory maintenance. The unit can deliver 6A continuous and 10A intermittent output load current and has output overload and over temperature protection with a fully automatic reset. The 24V input and 12V outputs share a common negative. The switching converter provides a low noise output closely regulated against variation of input voltage and changes in output load current. The unit is assembled in an aluminium extruded case. This allows for reliable operation in harsh vehicle environments and areas of high ambient temperatures.

EMC

Type approved to 72/245/EEC as last amended by 95/54/EC.

INPUT VOLTAGE

24 Volt nominal vehicle supply (20-32V).

OUTPUT VOLTAGE

12V \pm 5% @ 6A

OUTPUT LOAD CURRENT

Main: 6A continuous 10A intermittent.
Aux: 40mA continuous 2A intermittent.

NO LOAD INPUT CURRENT

Main: Maximum 130mA typical 90mA @ 24V input.
Aux: Maximum 10mA @ 24V input.

PROTECTION

Output overload and over temperature protection with fully automatic reset.

OPERATING TEMPERATURE

Maximum 70°C. Minimum -30°C

SIZE AND WEIGHT

Length: 100mm Height: 35mm Width: 60mm
180g

CONNECTIONS

200mm flying leads of thin wall auto cable.



24V Input		
Positive		red
Aux		white
12V Output		
Positive		blue
Aux		yellow
Common		black